

XLB-4319 Towable Boom with Hydraulic Outriggers



This lift features hydraulic outriggers which allow quick and easy setup. Proportional controls on this lift allow for smooth operation.

Advantage: The XLB-4319 offers a hydraulic jib for greater range of motion and the hydraulic basket rotation is used for precise overhead positioning, giving the operator access to a greater work area.

A large 450 lb. capacity cage and 110v outlet at the platform come standard on the XLB-4319. Also provided is a safety harness/lanyard and free backing brakes.

This lift is lightweight, allowing it to be towed by a variety of vehicles and easily maneuvered at the jobsite.

A spare tire/wheel assembly and spare tire mounting kit are offered as options.

This lift will even fit through double doors for indoor applications.

NOW ON ALL BIL-JAX BOOM LIFTS!

Outrigger LED Display

Located on the lower controls, this display indicates when each outrigger is properly set.

SPECIFICATIONS

Max. Working Height _____	43' (13.1m)
Max. Platform Height _____	37' (11.3m)
Max. Outreach _____	19' (5.8m)
Max. Cage Load _____	450 lbs. (204kg)
Rotation (noncontinuous) _____	700°
Power Option _____	24V DC w/ charger
Power Option _____	8HP Honda
Steel Cage Size _____	48" x 25" x 42" (1.1m x .65m x 1m)
Traveling Length _____	19' 5" (5.9m)
Traveling Height _____	6' 6" (2.0m)
Traveling Width _____	5' (1.5m)
Outrigger Footprint _____	9' 9" x 11' (3.0m x 3.4m)
Total Weight (DC) _____	2,860 lbs. (1300kg)
Total Weight (Gas) _____	3,200 lbs. (1455kg)
Tongue Weight _____	160 lbs. (73kg)
Brakes _____	Mechanical Surge with Parking Brake

RANGE OF MOTION

